



VIN-POE-162G1SF

1-16 Port: 100m Distance Full Gigabit PoE Switch



Main Feature:

- 16*1000Mbps PoE ports, 2*1000Mbps Uplink Port, 1*1000M SFP Port
- Support restrain network storm.
- Max Transmission distance up to 100m with PoE Power
- Built-in power supply
- Maximum power of single PoE port: 30W
- Maximum PoE power: 250W
- Adopts store-and-forward architecture
- Fanless, natural cooling, small, compact and quiet design, suitable for desktop or wall
- Support lightning protection 4000V

Feature	Specification
Power Adapter Voltage	AC 110V-240V
Consumption	300W(52V 5.76A)
PoE Ethernet Port	1-16 port:1000Mbps
Ethernet Port, SFP Port	Uplink port:10/100/1000Mbps, 1-SFP Port: 1000Mbps
Transmission Distance	1000Mbps:0-100m
Transmission Medium	Cat5/5e/6 standard network cable
Network Standard	IEEE802.3/802.3u,IEEE802.3x,IEEE802.3ab
Switching Capacity	38Gbps
Packet Buffer Memory	1Mbits
Throughput	29.41Mbps
MAC Table	4K
Packet Forwarding rate	10Mbps:14880pps/port, 100Mbps:148800pps/port, 1000Mbps: 1488000pps/port
PoE Standard	IEEE802.3af/at
PoE Power Supply	End-Span(1/2 + ; 3/6 -)
PoE Power	af=15.4w,at=30w for each port
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE802.3X Full-duplex and mode and back pressure for Half-duplex mode
LED Indicator	LINK/ACT 100Mbps: PoE Status Indicator, Power Indicator, Extender
Working temperature	0°C~55°C
Relative Humidity	20-95%
Storage temperature	-20°C~70°C
Dimension(L*W*H)	440mm*285mm*55mm
Color & Weight	Black 4.2Kg



*Product casing and specifications are subject to change without prior notice..

