



VS-POE-42065 DIAMOND-6K

1-4 Port: 180m Distance PoE Switch



Main Feature:

- 4*10/100Mbps PoE ports, 2*10/100Mbps uplink port
- Support IEEE802.3af/at;
- Support restrain network storm, VLAN & Watchdog function
- Max Transmission distance up to 180m with PoE Power
- Built-in power supply;
- Maximum power of single PoE port: 30W;
- Maximum PoE power: 65W;
- Adopts store-and-forward architecture;
- Fanless, natural cooling, small, compact and quiet design,
- suitable for desktop or wall;
- Support lightning Protection 6000V

Feature	Specification
Product type:	AI 100 Mbps POE Ethernet switch
Input voltage:	AC 100V-240V
Port Description:	4*10/100M PoE Ethernet port + 2*10/100M Uplink Ethernet ports
Total power consumption	Full load <65W
MTBF (Mean Time Between Failures)	100,000 hours
Working/Storage Temperature	30°C~ +70°C
Relative humidity	5% to 95% (no coagulation)
Power Indicator	PWR (Power Supply Indicator), red light (POE status indicator), blue light (link/data indicator)
Switching mode	Store-and-Forward
Packet forwarding rate	1.1904Mpps
Network Standards	IEEE802.3, IEEE802.3u, IEEE802.3x
Exchange capacity	1.6Gbps
Mac address Table	2k
Flow control	Support
Net topology	Supports star topology, bus topology, tree topology, and more
Levels of protection	IP30
Weight	0.35 kg per unit
Packing measurement	162x162x40mm
Casing	High-quality metal with superior heat dissipation
Power Budget	65W
Product size	130*110*35 mm (excluding protrusions)



*Product casing and specifications are subject to change without prior notice..